



Installation Instructions: Chevrolet Camaro 68-69, Chevrolet Nova 68-74 - Quad Console Pod



Model #10002 (small screws, washers)

1. Remove your existing Center Console. The gear shift cover plate must also be removed.
2. Remove the front console cover plate. For cars with the factory gauge option you must disconnect the gauge wiring.
WARNING: The Ammeter wiring **MUST** be properly disconnected (according to manufacturer specifications) to avoid danger of short circuit or fire.
3. Install new gauges into Console Pod and run the wiring through the center console.
4. Install Console Pod in the center console using supplied screws and washers. Reinstall the center console.
WARNING: Do not over-tighten screws. This may cause the threaded bushings to crack or break off.

Note: Due to normal manufacturing processes you may have "flashing" (small fibers of plastic) around the pod holes. Once the gauge(s) are installed in the pod you will not be able to see the "flashing."

Please contact Speedhut service department if you have a problem with this Product.

Speedhut Inc. 165 North 1330 West B2, Orem, Utah 84057 | support@speedhut.com | (801) 221-1460 (9am - 5pm MST) | www.Speedhut.com



Installation Instructions: Chevrolet Camaro 68-69, Chevrolet Nova 68-74 - Quad Console Pod



Model #10002 (small screws, washers)

1. Remove your existing Center Console. The gear shift cover plate must also be removed.
2. Remove the front console cover plate. For cars with the factory gauge option you must disconnect the gauge wiring.
WARNING: The Ammeter wiring **MUST** be properly disconnected (according to manufacturer specifications) to avoid danger of short circuit or fire.
3. Install new gauges into Console Pod and run the wiring through the center console.
4. Install Console Pod in the center console using supplied screws and washers. Reinstall the center console.
WARNING: Do not over-tighten screws. This may cause the threaded bushings to crack or break off.

Note: Due to normal manufacturing processes you may have "flashing" (small fibers of plastic) around the pod holes. Once the gauge(s) are installed in the pod you will not be able to see the "flashing."

Please contact Speedhut service department if you have a problem with this Product.

Speedhut Inc. 165 North 1330 West B2, Orem, Utah 84057 | support@speedhut.com | (801) 221-1460 (9am - 5pm MST) | www.Speedhut.com