

SPEEDHUT Installation Instructions: Pillars and Pods with Edge Attitude Mount

Installation Instructions: 07+ Chevy/GMC

Model #13012 and 13013 are designed Chevy 07+ (velcro and screw)

- STEP ONE:** Remove stock pillar (screw is located under the cap at the top of the pillar).
- STEP TWO:** Attach the two pieces of Velcro, peel one side and attach to recessed pocket area of the Attitude mount.
- STEP THREE:** Install Attitude in pillar, press firmly to engage adhesive to back of display (do not press on LCD).
- STEP FOUR:** Use provided screw to hold pillar in place: (Don't over tighten screw, Snug Only)

Installation Instructions: 99-02 Ford Super Duty

Model #13000 is designed to fit Ford SD 99-02 (velcro and ratchet fasteners)

- STEP ONE:** Attach the two Velcro pieces together. Peel back strip to expose adhesive from one side and attach to the recessed area of the mount where the Attitude fits.
- STEP TWO:** Expose adhesive and install Attitude in mount. Press firmly to engage adhesive to back of Display (Do not press on LCD).
- STEP THREE:** Run wires between mount and pillar (extra space has been provided for wires).
- STEP FOUR:** Place mount on A-pillar in final position.
- STEP FIVE:** Along the top of the mount, drill a 5/32" hole through the mount and A-pillar.
- STEP SIX:** Press in Ratchet Fasteners.

Installation Instructions: 03-06 Ford Super Duty

Model #13001 is designed to fit Ford SD 03-06 (velcro)

- STEP ONE:** Attach the two Velcro pieces together. Peel back strip to expose adhesive from one side and attach to the recessed area of the mount where the Attitude fits.
- STEP TWO:** Expose adhesive and install Attitude in mount. Press firmly to engage adhesive to back of Display (Do not press on LCD).
- STEP THREE:** Remove Handle from A-pillar (8mm bolts).
- STEP FOUR:** Run wires between mount and pillar (extra space has been provided for wires).
- STEP FIVE:** Place mount on pillar.
- STEP SIX:** Reinstall handle (The handle will catch the top edge of mount, holding it in place).

Installation Instructions: 03+ Dodge Ram

Model #13005 is designed to fit 2003+ Dodge Ram (velcro and long bolt)

- STEP ONE:** Attach the two Velcro pieces together. Peel back strip from one side and attach to the recessed area of the mount where the Attitude fits.
- STEP TWO:** Install Attitude in pod, press firmly to engage adhesive to back of Display.
-Do not press on LCD
- STEP THREE:** Run wires between mount and the stock A-pillar. There is a visible channel molded in for the wire.
- STEP FOUR:** Remove the lower cap and screw from the stock A-pillar handle.
- STEP FIVE:** Place mount over the stock A-pillar.
- STEP SIX:** Use provided (longer) screw to secure mount and A-pillar.

Installation Instructions: 98-02 Dodge Ram

Models #13008, #13009 are designed to fit 98-02 Dodge Ram (Velcro and ratchet fasteners)

Your new A-pillar mount installs over the factory A-pillar. It is not a replacement.

- STEP ONE:** Remove the stock A-pillar
- STEP TWO:** For models with the Infinity speaker, remove speaker from A-pillar. Cut or grind down the raised speaker hole on the stock A-pillar to allow the mounting of the new A-pillar mount.
- STEP THREE:** Hold the A-pillar mount in position on the factory A-pillar. Slight trimming of the A-pillar mount may be required for a perfect fit in some applications. Drill 3/16" holes through the 4 corners of both the mount and factory A-pillar.
- STEP FOUR:** Attach the two pieces of Velcro together. Peel back from one side and attach to the recessed area of the mount where the Attitude fits.
- STEP FIVE:** Install Attitude in pod, press firmly to engage adhesive to back of Display (**don't press on LCD**).
- STEP SIX:** The mount has clearance for the Attitude wires to be run down the back and through the bottom. Secure wiring to the back of the new mount.
- STEP SEVEN:** Insert ratchet fasteners through holes to attach mount to factory A-pillar.
- STEP EIGHT:** Re-install mount/factory A-pillar assembly, making sure wires are not pinched.

SPEEDHUT Installation Instructions: Ford Super Duty 99-06 overhead console mount

Model #13002 are designed to fit 99-06 Ford Super Duty (2 velcro strips)

STEP ONE: Attach the two Velcro pieces together. Peel back strip to expose adhesive from one side and attach to the recessed area of the mount where the Attitude fits.

STEP TWO: Expose adhesive and install Attitude in mount. Press firmly to engage adhesive to back of Display.
(Do not press on LCD)

STEP THREE: Apply Velcro to rear of Pod.

STEP FOUR: Clean window area where Velcro attaches.

STEP FIVE: Peel backing off Velcro.
Note: In step 6 be careful not to let Velcro touch windshield.

STEP SIX: Insert top edge of pod back into the space between the windshield and the metal roof edge, located under the headliner.

STEP SEVEN: Feed wiring under headliner for several inches and slide pod into position above rear view mirror.

STEP EIGHT: Push pod firmly up against head liner.

STEP NINE: With pod firmly against head liner, press bottom of pod against windshield, apply firm pressure to bond Velcro to window.
Note: Hold firm pressure for at least one minute. Continue running wiring under headliner and down a-pillar.

www.Speedhut.com **Need help?** Contact us: Speedhut Inc. 165 North 1330 West B2 Orem, Utah 84057 or call 801-221-1460

SPEEDHUT Installation Instructions: Ford Super Duty 99-06 overhead console mount

Model #13002 are designed to fit 99-06 Ford Super Duty (2 velcro strips)

STEP ONE: Attach the two Velcro pieces together. Peel back strip to expose adhesive from one side and attach to the recessed area of the mount where the Attitude fits.

STEP TWO: Expose adhesive and install Attitude in mount. Press firmly to engage adhesive to back of Display.
(Do not press on LCD)

STEP THREE: Apply Velcro to rear of Pod.

STEP FOUR: Clean window area where Velcro attaches.

STEP FIVE: Peel backing off Velcro.
Note: In step 6 be careful not to let Velcro touch windshield.

STEP SIX: Insert top edge of pod back into the space between the windshield and the metal roof edge, located under the headliner.

STEP SEVEN: Feed wiring under headliner for several inches and slide pod into position above rear view mirror.

STEP EIGHT: Push pod firmly up against head liner.

STEP NINE: With pod firmly against head liner, press bottom of pod against windshield, apply firm pressure to bond Velcro to window.
Note: Hold firm pressure for at least one minute. Continue running wiring under headliner and down a-pillar.

www.Speedhut.com **Need help?** Contact us: Speedhut Inc. 165 North 1330 West B2 Orem, Utah 84057 or call 801-221-1460